

# PERF-O GRIP SAFETY GRATING STAIR TREADS



\* 2" Channel Height 0.125" Aluminum 5052-H32

| Perf-O Grip Recommended Sizes & Spans |                  |                   |                |       |
|---------------------------------------|------------------|-------------------|----------------|-------|
| Span in.                              | Material / Gauge | Channel Depth in. | Catalog Number | Width |
| Up to 30"                             | Steel 13 ga.     | 1-1/2"            | T-P21513       | 5"    |
|                                       |                  |                   | T-P31513       | 7"    |
|                                       |                  |                   | T-P51513       | 10"   |
|                                       |                  |                   | T-P61513       | 12"   |
| 31" to 48"                            | Steel 11 ga.     | 2"                | T-P22011       | 5"    |
|                                       |                  |                   | T-P32011       | 7"    |
|                                       |                  |                   | T-P52011       | 10"   |
|                                       |                  |                   | T-P62011       | 12"   |
| Up to 42"                             | Alum. .125       | 2"                | T-P220.125-A   | 5"    |
|                                       |                  |                   | T-P320.125-A   | 7"    |
|                                       |                  |                   | T-P520.125-A   | 10"   |
|                                       |                  |                   | T-P620.125-A   | 12"   |

\*Intermediate supports recommended for all treads spanning greater than 48 inches (42 inches for aluminum treads).

| Perf-O Grip Stair Tread Widths |           |        |      |    |
|--------------------------------|-----------|--------|------|----|
| Product Width                  | A         | B      | C    | D  |
| 2-Hole<br>5"                   | 4-15/16"  | 1-1/2" | 3/4" | 2" |
| 3-Hole<br>7"                   | 6-15/16"  | 1-1/2" | 3/4" | 4" |
| 5-Hole<br>10"                  | 9-15/16"  | 1-1/2" | 3/4" | 7" |
| 6-Hole<br>12"                  | 11-15/16" | 1-1/2" | 3/4" | 9" |

